

# TRAVERTINE CLASSICO™

Technical Data Sheet A.1



Travertine Classico™ is quarried in the Aegean region of Turkey. It is quarried in blocks, cut down to tile sizes, polished to a honed finish (satin matt) and filled mechanically with a mixture of calcite powder, kaolin, white cement and bonding agents. This mix is a durable, compatible filler that is colour matched to the stone. The stone and filler take 6-8 weeks to dry to final colour.

**Classico™ Light** offers the lightest shading in the range with a light to medium beige colour and slight possibility of brownish veining. The ratio of homogeneity is 70%. **Classico™** encompasses shades from light-medium to medium-dark beige with a possibility of brownish veining. The ratio of homogeneity is 50%. **Classico™ Commercial** is a mixed commercial selection of the Classico™ range. The colour can vary from light to medium beige with a high possibility of brownish to black veining. The ratio of homogeneity is 30%.

# TRAVERTINE CLASSICO™

Technical Data Sheet A.1

## SIZES

280 x 280 x 10 mm	610 x 305 x 15 mm	610 x 610 x 15 mm
305 x 305 x 10 mm	610 x 406 x 15 mm	1000 x 610 x 15 mm
305 x 305 x 12 mm	610 x 457 x 15 mm	20mm slabs
406 x 406 x 12 mm	610 x 508 x 15 mm	30mm slabs
457 x 457 x 12 mm		

## RECOMMENDED APPLICATIONS

This product is best suited for interior use on floors and walls. It can be used virtually anywhere in the house from kitchen or bathroom to lounge and dining room. The product can also be used externally for walls. The filled and honed tiles can be slippery under extremely wet conditions and are not recommended for exterior use on floors. Instead we recommend using tiles from the Rustico™ or Antico™ ranges (see Technical Data Sheets A.3 and A.4, respectively).

## LAYING RECOMMENDATION

- A 2-3mm joint between tiles
- The use of white tile adhesive
- MCC Travertine grout
- Existing expansion joints should be respected and not tiled over
- Use expansion joints as prescribed by architect or specialized tiler
- Tiles should be laid on a level and even screed which should have been cured for about one week prior to tiling

## PRODUCT CARE & MAINTENANCE

All natural stone should be sealed to prevent staining. We recommend the use of Delta Research Seal or Saf Seal as an anti-stain treatment. The product must be applied by professionals or under strict instruction as indicated by Delta Research. For everyday maintenance we recommend Delta Research Clean Stone or a neutral pH detergent. Do not use acid or alkaline detergents as repeated applications will damage the sealer, leaving the stone unprotected. Acid products can also erode the filler.

NATURAL STONE  
WAREHOUSE

www.naturalstonewarehouse.com