

# GRANITE



One of the hardest natural stones available, Granite is an extremely versatile product, suitable for floor and wall tiles as well as counter tops. It is available in a number of colours and finishes, including flamed and bush hammered, which make for perfect outdoor tiles due to their excellent non slip qualities.



CAPE TOWN 021 506 1300 | GAUTENG 011 704 6827  
KNYSNA 044 382 3632 | DURBAN 031 566 6562

[www.naturalstonewarehouse.com](http://www.naturalstonewarehouse.com)

# GRANITE

## SIZES

Enquire at any one of our showrooms for available sizes.

---

## RECOMMENDED APPLICATIONS

Granite can be used in both interior and exterior applications. The honed and polished finishes are recommended for indoor use, while the flamed and bush hammered finishes, due to their uneven surface texture, are perfect for outdoor use and provide an excellent slip resistant finish.

As this is a natural product, one can expect slight colour variations between batches. Please arrange a product preview, either by photograph, or at one of our distribution centres in order to view the current stock.

---

## LAYING RECOMMENDATION

- A 5-10mm joint between tiles - We do not recommend butt joining tiles  
Larger format tiles require a minimum of 10mm joint thickness
  - The use of Grey tile adhesive
  - Grey quarry Grout or grout colour to individual taste
  - No acid is to be used in the removing of grout/adhesive residue
  - Existing expansion joints are to be respected and not tiled over
  - Use expansion joints as prescribed by architect or specialized tiler
  - Tiles should be laid on a level and even screed which should have been cured for about one week before tiling
  - Naturally each piece is unique in veining and tonality therefore the onus rest with the installer to ensure blending is done correctly before laying the tiles to achieve your desired effect.
- 

## PRODUCT CARE AND MAINTENANCE

All natural stone tiles should be sealed to prevent staining. The laid tiles should be washed with Stone Shield Deep Clean which is a stone detergent. The tiler must ensure that no grout or adhesive is allowed to dry on the tile surface. After washing and rinsing the stone must be left to dry completely including grouting. As an anti-stain treatment we recommend the use of Stone Shield Marble, Granite and Travertine sealer. The product must be applied by professionals or under the strict instruction as indicated by the manufacturer. Sealers may cause enhancement of the natural colours of the stone depending on the stone type and the sealer used. Please speak to a consultant should you wish to have a demonstration of the finished product.

For everyday maintenance we recommend Stone Shield Daily Clean or a neutral Ph detergent. Do not use acid or alkaline detergents as repeated application will damage the sealer leaving the stone unprotected.



Remember to ask us about your warranty options.

The colours shown on this spec sheet are as exact as photographic and printing processes as well as screen resolution allow. We recommend that all colours are chosen from actual product samples available on request.

Pioneers in the art of elegant living.